

IN THE CLAIMS

The following is a complete listing of the claims:

Claims 1-13 (canceled)

14. (original) In a communication device, a method for determining an operating frequency of an oscillator based on a reference signal from a reliable time base, comprising:

detecting a beginning time point of the reference signal received by the communication device;

upon detection of the beginning time point of the reference signal, enabling a counter to count in accordance with a clock signal derived from the oscillator;

detecting an ending time point of the reference signal received by the communication device;

upon detecting the ending time point of the reference signal, disabling the counter to stop the counter from further counting; and

determining the frequency of the oscillator based on the count in the counter and an expected time that elapsed between the beginning time point and the ending time point.

15. (original) A method as in Claim 14, wherein the beginning time point and the ending time point represent a known duration in time.

16. (original) A method as in Claim 14, wherein the beginning time point and the ending time point represent arrivals of recurring events in the reference signal, the recurring events recurs at a fixed frequency.

17. (original) A method as in Claim 14, further comprising adjusting for processing times in the communication device for detecting the beginning time point and the ending time point.

18. (cancelled)

19. (cancelled)

LAW OFFICES OF
MACPHERSON, KWOK CHEN
& HEJO LLP
1762 TECHNOLOGY DRIVE
SUITE 220
SAN JOSE, CA 95110
(415) 737-7040
FAX (408) 393-8262

20. (original) A method as in Claim 14, wherein the frequency of the oscillator thus determined is provided to a positioning signal receiver.

21. (original) A method as in Claim 20, wherein the positioning signal receiver receives global positioning system (GPS) signals.

Claims 22-33 (canceled)

34. (currently amended) An oscillator frequency determining apparatus in a communication device, comprising:

an oscillator providing a periodic output signal;

a receiver receiving a reference signal from a reliable time base;

a detector detecting a beginning time point and an ending time point of the reference signal received by the communication device;

a counter that begins counting the number of periods in the output signal of the oscillator in response to the detector detecting the beginning time point and stops counter counting in response to the detector detecting the ending time point of the reference signal; and

an arithmetic unit for determining the frequency of the oscillator based on the count in the counter and an expected time that elapsed between the beginning time point and the ending time point.

35. (original) An apparatus as in Claim 34, wherein the beginning time point and the ending time point represent a known duration in time.

36. (original) An apparatus as in Claim 34, wherein the beginning time point and the ending time point represent arrivals of recurring events in the reference signal, the recurring events recurs at a fixed frequency.

37. (original) An apparatus as in Claim 34, wherein the arithmetic unit further adjusts for processing times in the communication device for detecting the beginning time point and the ending time point.

38. (cancelled)

39. (cancelled)

LAW OFFICES OF
MACPHERSON, KWOK CHEN
& HEID LLP

1762 TECHNOLOGY DRIVE
SUITE 326
SAN JOSE, CA 95110
(415) 752-7040
FAX (408) 392-9262

40. (original) An apparatus as in Claim 34, wherein the frequency of the oscillator thus determined is provided to a positioning signal receiver.

41. (original) An apparatus as in Claim 40, wherein the positioning signal receiver receives global positioning system (GPS) signals.

LAW OFFICES OF
MACPILSON, KWOK CHEN
& HEID LLP

1702 TECHNOLOGY DRIVE
SUITE 226
SAN JOSE, CA 95110
(408) 752-7040
FAX (408) 391-9267